

**Integrated AMSU-A**  
**Earth Observing System (EOS)**  
**Advanced Microwave Sounding Unit-A (AMSU-A)**

**Engineering Telemetry Description**

**Contract No. NAS 5-32314**  
**CDRL 305**

**Submitted to:**

**National Aeronautics and Space Administration**  
**Goddard Space Flight Center**  
**Greenbelt, Maryland 20771**

**Submitted by:**

**Aerojet**  
**1100 West Hollyvale Street**  
**Azusa, California 91702**

## TABLE OF CONTENTS

| Paragraph |  | Page |
|-----------|--|------|
| 1.        | SCOPE .....                                    | 1    |
| 2.        | EOS/AMSU-A TELEMETRY LIST AND DESCRIPTION..... | 2    |
| 2.1       | Passive Analog Telemetry.....                  | 2    |
| 2.2       | Engineering Telemetry Data .....               | 2    |
| 2.2.1     | Analog Telemetry Data .....                    | 2    |
| 2.2.2     | Digital Telemetry Data .....                   | 12   |
| 2.2.3     | Data Word Format .....                         | 13   |

## TABLES

|         |  |    |
|---------|--|----|
| Table 1 | Passive Analog Telemetry Data Limits for AMSU-A1 ..... | 3  |
| Table 2 | Passive Analog Telemetry Data Limits for AMSU-A2 ..... | 4  |
| Table 3 | EOS/AMSU-A1 Engineering Telemetry Data and Limits..... | 5  |
| Table 4 | EOS/AMSU-A2 Engineering Telemetry Data and Limits..... | 8  |
| Table 5 | Data Word Format .....                                 | 13 |

## FIGURES

|           |                                      |    |
|-----------|--------------------------------------|----|
| Figure 1  | EOS/AMSU – A1 Command / Status ..... | 7  |
| Figure 2. | EOS/AMSU – A2 Command / Status ..... | 10 |

## **SECTION 1**

### **1. SCOPE**

This document "Engineering Telemetry Description" contains description of the telemetry provided by EOS/AMSU-A instrument, which shall be monitored to evaluate operation and status of the instrument during instrument spacecraft integration, acceptance/qualification testing and in-orbit operation. The "Engineering Telemetry Description" is the submittal in response to Contract NAS5-32314, CDRL 305.

## SECTION 2

### EOS/AMSU-A TELEMETRY LIST AND DESCRIPTION

#### 2. EOS/AMSU-A TELEMETRY

EOS/AMSU-A provides 1) Passive Analog and 2) Engineering Telemetry Data.

##### 2.1 PASSIVE ANALOG TELEMETRY

The passive analog telemetry are provided to sample critical temperatures within the instrument. These are tabulated in Table 1 and Table 2 for AMSU-A1 and AMSU-A2 respectively. Mission critical thermistors are the RF shelf temperatures and redundancy is provided for these critical thermistors. EOS/AMSU-A1 and AMSU-A2 passive analog telemetry lists and limits are provided in Table 1 and Table 2 respectively. Also, passive analog telemetry will provide passive indicators for Bus A and Bus B. Temperature vs. resistance curves for each temperature sensor will be provided in calibration log book.

##### 2.2 ENGINEERING TELEMETRY DATA

Engineering Telemetry data consists of analog telemetry and digital telemetry. The Engineering telemetry data list and limits are provided in Table 3 and Table 4 for AMSU-A1 and AMSU-A2 respectively.

###### 2.2.1 ANALOG TELEMETRY DATA

Analog telemetry data transmitted from the EOS/AMSU-A instrument consist of secondary voltages, bus currents, and instrument temperatures. These parameters are multiplexed, digitized, and made available to the spacecraft via the MIL-STD-1553 bus as Engineering data.

###### 2.2.1.1 Instrument temperature sensors:

For instrument temperature sensors (refer to data word 13 through 57, Table 3 and data word 12 through 30, Table 4) parameter is defined by a set of functions. The coefficients will be provided in calibration logbook for each PRT temperature sensor.

Platinum resistance temperature sensors (PRTs) are used throughout the instrument to monitor key temperatures. These sensors each have unique coefficients based on the manufacturer's data. PRT circuit calibration is performed during the instrument integration level test.

**Table 1 PASSIVE ANALOG TELEMETRY DATA LIMITS FOR AMSU-AI**

| J2 PIN<br>NUMBER |     | DESCRIPTION                    | Red Limit<br>(LOW) | Yellow Limit<br>(LOW) | Yellow Limit<br>(High) | Red Limit<br>(High) |
|------------------|-----|--------------------------------|--------------------|-----------------------|------------------------|---------------------|
| HI               | LOW |                                | Deg. C             | Deg. C                | Deg. C                 | Deg. C              |
| 1                | 2   | A 1 -1 Scan Motor Temperature  | -30                | -20                   | 58                     | 66                  |
| 7                | 8   | A 1 -2 Scan Motor Temperature  | -30                | -20                   | 58                     | 66                  |
| 3                | 4   | A 1-1 RF Shelf Temperature # 1 | -30                | -20                   | 58                     | 66                  |
| 9                | 10  | A1-2 RF Shelf Temperature #1   | -30                | -20                   | 58                     | 66                  |
| 5                | 6   | A1-1 Warm Load Temperature     | -30                | -20                   | 58                     | 66                  |
| 11               | 12  | A1-2 Warm Load Temperature     | -30                | -20                   | 58                     | 66                  |
| 22               | 23  | A1-1 RF Shelf Temperature #2   | -30                | -20                   | 58                     | 66                  |
| 28               | 29  | A1S-2 RF Shelf Temperature #2  | -30                | -20                   | 58                     | 66                  |
| 19               | 18  | Quiet Bus Indicator*           | N/A                | N/A                   | N/A                    | N/A                 |
| 37               | 36  | Noisy Bus Indicator"           | N/A                | N/A                   | N/A                    | N/A                 |

\*Quiet Bus Indicator

Bus A  $1K\Omega \pm 10\%$

Bus B  $2K\Omega \pm 10\%$

\*\*Noisy Bus Indicator

Bus A  $1K\Omega \pm 10\%$

Bus B  $2K\Omega \pm 10\%$

**Table 2 PASSIVE ANALOG TELEMETRY DATA LIMITS FOR AMSU-A2**

| J2 PIN<br>NUMBER |     | DESCRIPTION             | Red Limit<br>(Low)<br>Deg. C | Yellow Limit<br>(Low)<br>Deg. C | Yellow Limit<br>(High)<br>Deg. C | Red Limit<br>(High)<br>Deg. C |
|------------------|-----|-------------------------|------------------------------|---------------------------------|----------------------------------|-------------------------------|
| HI               | LOW |                         |                              |                                 |                                  |                               |
| 1                | 2   | Scan Motor Temperature  | -30                          | -20                             | 58                               | 66                            |
| 3                | 4   | RF Shelf Temperature #1 | -30                          | -20                             | 58                               | 66                            |
| 5                | 6   | Warm Load Temperature   | -30                          | -20                             | 58                               | 66                            |
| 22               | 23  | RF Shelf Temperature #2 | -30                          | -20                             | 58                               | 66                            |
| 19               | 18  | Quiet Bus Indicator*    | N/A                          | N/A                             | N/A                              | N/A                           |
| 37               | 36  | Noisy Bus Indicator**   | N/A                          | N/A                             | N/A                              | N/A                           |

\*Quiet Bus Indicator

Bus A  $1K\Omega \pm 10\%$

Bus B  $2K\Omega \pm 10\%$

\*\*Noisy Bus Indicator

Bus A  $1K\Omega \pm 10\%$

Bus B  $2K\Omega \pm 10\%$

Table 3 (Page 1 of 2)

EOS/AMSU-A1 ENGINEERING TELEMETRY DATA AND LIMITS

| DATA WORD | FUNCTION MONITORED                             | UNIT | INDICATOR LIMIT (LOW) | LOW* LIMIT | NOMINAL @ | HIGH* LIMIT | INDICATOR LIMIT (HIGH) |
|-----------|--|------|-----------------------|------------|-----------|-------------|------------------------|
| 1         | Primary Header - Packet ID                     |      |                       |            | N/A       |             |                        |
| 2         | Primary Header - Packet Sequence Control       |      |                       |            | N/A       |             |                        |
| 3         | Primary Header - Packet Length                 |      |                       |            | N/A       |             |                        |
| 4         | Secondary Header                               |      |                       |            | N/A       |             |                        |
| 5         | Secondary Header                               |      |                       |            | N/A       |             |                        |
| 6         | Secondary Header                               |      |                       |            | N/A       |             |                        |
| 7         | Secondary Header                               |      |                       |            | N/A       |             |                        |
| 8         | Secondary Header (Plus one dummy zero byte)    |      |                       |            | N/A       |             |                        |
| 9         | Unit Serial Number                             |      |                       |            | N/A       |             |                        |
| 10        | Instrument Mode and Relay Status               |      | N/A                   | N/A        | FIGURE 1  | N/A         | N/A                    |
| 11        | Reflector Position (A1-1 Antenna)              | CO   | N/A                   | m-8        | m         | m+16        | N/A                    |
| 12        | Reflector Position (A1-2 Antenna)              | CO   | N/A                   | n-8        | n         | n+16        | N/A                    |
| 13        | 1 Scan Motor A1-1 Temperature                  | °C   | -10                   | N/A        |           | N/A         | +48                    |
| 14        | 2 Scan Motor A1-2 Temperature                  | °C   | -10                   | N/A        |           | N/A         | +48                    |
| 15        | 3 Feedhorn A1-1                                | °C   | -10                   | N/A        |           | N/A         | +48                    |
| 16        | 4 Feedhorn A1-2                                | °C   | -10                   | N/A        |           | N/A         | +48                    |
| 17        | 5 RF Mux - A1-1 Temperature                    | °C   | -10                   | N/A        |           | N/A         | +48                    |
| 18        | 6 RF Mux - A1-2 Temperature                    | °C   | -10                   | N/A        |           | N/A         | +48                    |
| 19        | 7 Local Oscillator - Channel 3 Temperature     | °C   | -10                   | -1         |           | +44         | +48                    |
| 20        | 8 Local Oscillator - Channel 4 Temperature     | °C   | -10                   | -1         |           | +44         | +48                    |
| 21        | 9 Local Oscillator - Channel 5 Temperature     | °C   | -10                   | -1         |           | +44         | +48                    |
| 22        | 10 Local Oscillator - Channel 6 Temperature    | °C   | -10                   | -1         |           | +44         | +48                    |
| 23        | 11 Local Oscillator - Channel 7 Temperature    | °C   | -10                   | -1         |           | +44         | +48                    |
| 24        | 12 Local Oscillator - Channel 8 Temperature    | °C   | -10                   | -1         |           | +44         | +48                    |
| 25        | 13 Local Oscillator - Channel 15 Temperature   | °C   | -10                   | -1         |           | +44         | +48                    |
| 26        | 14 Phase Locked Oscillator No. 2 Temperature   | °C   | -10                   | +1         |           | +44         | +48                    |
| 27        | 15 Phase Locked Oscillator No. 1 Temperature   | °C   | -10                   | +1         |           | +44         | +48                    |
| 28        | 16 S.P. (1553 Interface) Temperature           | °C   | -10                   | N/A        |           | N/A         | +52                    |
| 29        | 17 Mixer/IF Amplifier - Channel 3 Temperature  | °C   | -10                   | N/A        |           | N/A         | +48                    |
| 30        | 18 Mixer/IF Amplifier - Channel 4 Temperature  | °C   | -10                   | N/A        |           | N/A         | +48                    |
| 31        | 19 Mixer/IF Amplifier - Channel 5 Temperature  | °C   | -10                   | N/A        |           | N/A         | +48                    |
| 32        | 20 Mixer/IF Amplifier - Channel 6 Temperature  | °C   | -10                   | N/A        |           | N/A         | +48                    |
| 33        | 21 Mixer/IF Amplifier - Channel 7 Temperature  | °C   | -10                   | N/A        |           | N/A         | +48                    |
| 34        | 22 Mixer/IF Amplifier - Channel 8 Temperature  | °C   | -10                   | N/A        |           | N/A         | +48                    |
| 35        | 23 Mixer/IF Amplifier - Channel 9/14 Temp      | °C   | -10                   | N/A        |           | N/A         | +48                    |
| 36        | 24 Mixer/IF Amplifier - Channel 15 Temperature | °C   | -10                   | N/A        |           | N/A         | +48                    |
| 37        | 25 IF Amp - Channel 11/14 Temperature          | °C   | -10                   | N/A        |           | N/A         | +48                    |
| 38        | 26 IF Amp - Channel 9 Temperature              | °C   | -10                   | N/A        |           | N/A         | +48                    |
| 39        | 27 IF Amp - Channel 10 Temperature             | °C   | -10                   | N/A        |           | N/A         | +48                    |
| 40        | 28 IF Amp - Channel 11 Temperature             | °C   | -10                   | N/A        |           | N/A         | +48                    |
| 41        | 29 DC/DC Converter Temperature                 | °C   | -10                   | N/A        |           | N/A         | +48                    |

\* INSTRUMENT WITHIN SPECIFICATION

@ Nominal values for reflector position (m & n) will be provided in Calibration Log Book. Nominal values for temperatures will be provided after completion of thermal balance test. All other nominal values will be provided after first Comprehensive Performance Test.

Table - 3 (Page 2 of 2)

EOS/AMSU-AI ENGINEERING TELEMETRY DATA AND LIMITS


| DATA WORD | FUNCTION MONITORED                      | UNIT | INDICATOR LIMIT (LOW) | LOW* LIMIT | NOMINAL @ | HIGH* LIMIT | INDICATOR LIMIT (HIGH) |
|-----------|---|------|-----------------------|------------|-----------|-------------|------------------------|
| 42        | 30 IF Amp - Channel 13 Temperature      | °C   | -10                   | N/A        |           | N/A         | +48                    |
| 43        | 31 IF Amp - Channel 14 Temperature      | °C   | -10                   | N/A        |           | N/A         | +48                    |
| 44        | 32 IF Amp - Channel 12 Temperature      | °C   | -10                   | N/A        |           | N/A         | +48                    |
| 45        | 33 RF Shelf - AI-1 Temperature          | °C   | -10                   | -2         |           | +38         | +48                    |
| 46        | 34 RF Shelf - AI-2 Temperature          | °C   | -10                   | -2         |           | +38         | +48                    |
| 47        | 35 Detector/Preamplifier Temperature    | °C   | -10                   | N/A        | N/A       | N/A         | +48                    |
| 48        | 36 AI-1 Warm Load 1 Temperature         | °C   | -15                   | N/A        | N/A       | N/A         | +40                    |
| 49        | 37 AI-1 Warm Load 2 Temperature         | °C   | -15                   | N/A        | N/A       | N/A         | +40                    |
| 50        | 38 AI-1 Warm Load 3 Temperature         | °C   | -15                   | N/A        | N/A       | N/A         | +40                    |
| 51        | 39 AM Warm Load 4 Temperature           | °C   | -15                   | N/A        | N/A       | N/A         | +40                    |
| 52        | 40 AI-1 Warm Load Center Temperature    | °C   | -15                   | N/A        | N/A       | N/A         | +40                    |
| 53        | 41 AI-2 Warm Load 1 Temperature         | °C   | -15                   | N/A        | N/A       | N/A         | +40                    |
| 54        | 42 AI-2 Warm Load 2 Temperature         | °C   | -15                   | N/A        | N/A       | N/A         | +40                    |
| 55        | 43 AI-2 Warm Load 3 Temperature         | °C   | -15                   | N/A        | N/A       | N/A         | +40                    |
| 56        | 44 AI-2 Warm Load 4 Temperature         | °C   | -15                   | N/A        | N/A       | N/A         | +40                    |
| 57        | 45 AI-2 Warm Load Center Temperature    | °C   | -15                   | N/A        | N/A       | N/A         | +40                    |
| 58        | PRT Reference Voltage                   | CO   | N/A                   | N/A        |           | N/A         | N/A                    |
| 59        | Signal Processor +5 Volts               | V    | N/A                   | +4         | +5        | +6          | N/A                    |
| 60        | Signal Processor +15 Volts              | V    | N/A                   | +14        | +15       | +16         | N/A                    |
| 61        | Signal Processor -15 Volts              | V    | N/A                   | -16        | -15       | -14         | N/A                    |
| 62        | Scan Drive +5 Volts                     | V    | N/A                   | +4         | +5        | +6          | N/A                    |
| 63        | Scan Drive +15 Volts                    | V    | N/A                   | +13        | +15       | +17         | N/A                    |
| 64        | Scan Drive -15 Volts                    | V    | N/A                   | -17        | -15       | -13         | N/A                    |
| 65        | PLO +15 Volts                           | V    | N/A                   | +14        | +15       | +16         | N/A                    |
| 66        | PLO -15 Volts                           | V    | N/A                   | -16        | -15       | -14         | N/A                    |
| 67        | Receiver +8 Volts                       | V    | N/A                   | +7         | +8        | +9          | N/A                    |
| 68        | Mixer/IF Amplifier - AI-1 +10 Volts     | V    | N/A                   | +9         | +10       | +11         | N/A                    |
| 69        | Mixer/IF Amplifier - AI-2 +10 Volts     | V    | N/A                   | +9         | +10       | +11         | N/A                    |
| 70        | Local Oscillator - Channel 6 +10 Volts  | V    | N/A                   | +9         | +10       | +11         | N/A                    |
| 71        | Local Oscillator - Channel 7 +10 Volts  | V    | N/A                   | +9         | +10       | +11         | N/A                    |
| 72        | Spare                                   | V    | N/A                   | N/A        | N/A       | N/A         | N/A                    |
| 73        | Local Oscillator - Channel 3 +10 Volts  | V    | N/A                   | +9         | +10       | +11         | N/A                    |
| 74        | Local Oscillator - Channel 4 +10 Volts  | V    | N/A                   | +9         | +10       | +11         | N/A                    |
| 75        | Local Oscillator - Channel 5 +10 Volts  | V    | N/A                   | +9         | +10       | +11         | N/A                    |
| 76        | Local Oscillator - Channel 8 +10 Volts  | V    | N/A                   | +9         | +10       | +11         | N/A                    |
| 77        | Local Oscillator - Channel 15 +15 Volts | V    | N/A                   | +14        | +15       | +16         | N/A                    |
| 78        | AI Quiet Bus Current                    | A    | N/A                   | N/A        |           | 3.21        | N/A                    |
| 79        | AI-1 Noisy Power Bus Current            | A    | N/A                   | N/A        |           | 0.107       | N/A                    |
| 80        | AI-2 Noisy Power Bus Current            | A    | N/A                   | N/A        |           | 0.107       | N/A                    |

V =Vdc

A = Ampere

CO = Counts





| * Cold Cal Pos. | MSB | LSB |
|-----------------|-----|-----|
| 1               | 0   | 0   |
| 2               | 0   | 1   |
| 3               | 1   | 0   |
| 4               | 1   | 1   |

Figure 1 EOS/AMSU – A1 Command / Status

**Table 4 EOS/AMSU-A2 ENGINEERING TELEMETRY DATA AND LIMITS**

| DATA WORD | FUNCTION MONITORED                           | UNIT | INDICATOR LIMIT (LOW) | LOW* LIMIT | NOMINAL @ | HIGH* LIMIT | INDICATOR LIMIT (HIGH) |
|-----------|--|------|-----------------------|------------|-----------|-------------|------------------------|
| 1         | Primary Header - Packet ID                   |      |                       |            | N/A       |             |                        |
| 2         | Primary Header - Packet Sequence Control     |      |                       |            | N/A       |             |                        |
| 3         | Primary Header - Packet Length               |      |                       |            | N/A       |             |                        |
| 4         | Secondary Header                             |      |                       |            | N/A       |             |                        |
| 5         | Secondary Header                             |      |                       |            | N/A       |             |                        |
| 6         | Secondary Header                             |      |                       |            | N/A       |             |                        |
| 7         | Secondary Header                             |      |                       |            | N/A       |             |                        |
| 8         | Secondary Header (Plus one dummy zero byte)  |      |                       |            | N/A       |             |                        |
| 9         | Unit Serial Number                           |      |                       |            | N/A       |             |                        |
| 10        | Instrument Mode and Relay Status             |      | N/A                   | N/A        | FIGURE 2  | N/A         | N/A                    |
| 11        | Reflector Position                           | CO   | N/A                   | m-8        | m         | m+16        | N/A                    |
| 12        | 1 Scan Motor AM Temperature                  | °C   | -10                   | N/A        |           | N/A         | +48                    |
| 13        | 2 Feedhorn Temperature                       | °C   | -10                   | N/A        |           | N/A         | +48                    |
| 14        | 3 RF Diplexer Temperature                    | °C   | -10                   | N/A        |           | N/A         | +48                    |
| 15        | 4 Mixer/IF Amplifier - Channel 1 Temperature | °C   | -10                   | N/A        |           | N/A         | +48                    |
| 16        | 5 Mixer/IF Amplifier - Channel 2 Temperature | °C   | -10                   | N/A        |           | N/A         | +48                    |
| 17        | 6 Local Oscillator - Channel 1 Temperature   | °C   | -10                   | -5         |           |             | +48                    |
| 18        | 7 Local Oscillator - Channel 2 Temperature   | °C   | -10                   | -5         |           |             | +48                    |
| 19        | 8 S.P. (1553 Interface) Temperature          | °C   | -10                   | N/A        |           |             | +52                    |
| 20        | 9 Subreflector Temperature                   | °C   | -10                   | N/A        |           |             | +48                    |
| 21        | 10 DOM Converter Temperature                 | °C   | -10                   | N/A        |           |             | +48                    |
| 22        | 11 RF Shelf - Temperature                    | °C   | -10                   | -7         |           |             | +48                    |
| 23        | 12 Detector/Preamplifier Temperature         | °C   | -10                   | N/A        |           | N/A         | +48                    |
| 24        | 13 Warm Load Center Temperature              | °C   | -15                   | N/A        | N/A       | N/A         | +40                    |
| 25        | 14 Warm Load 2 Temperature                   | °C   | -15                   | N/A        | N/A       | N/A         | +40                    |
| 26        | 15 Warm Load 3 Temperature                   | °C   | -15                   | N/A        | N/A       | N/A         | +40                    |
| 27        | 16 Warm Load 4 Temperature                   | °C   | -15                   | N/A        | N/A       | N/A         | +40                    |
| 28        | 17 Warm Load 5 Temperature                   | °C   | -15                   | N/A        | N/A       | N/A         | +40                    |
| 29        | 18 Warm Load 6 Temperature                   | °C   | -15                   | N/A        | N/A       | N/A         | +40                    |
| 30        | 19 Warm Load 1 Temperature                   | °C   | -15                   | N/A        | N/A       | N/A         | +40                    |
| 31        | PRT Reference Voltage                        | CO   | N/A                   | N/A        |           | N/A         | N/A                    |
| 32        | Signal Processor +5 Volts                    | V    | N/A                   | +4         | +5        | +6          | N/A                    |
| 33        | Signal Processor +15 Volts                   | V    | N/A                   | +14        | +15       | +16         | N/A                    |
| 34        | Signal Processor - 15 Volts                  | V    | N/A                   | -16        | -15       | -14         | N/A                    |
| 35        | Scan Drive +5 Volts                          | V    | N/A                   | +4         | +5        | +6          | N/A                    |
| 36        | Scan Drive +15 Volts                         | V    | N/A                   | +13        | +15       | +17         | N/A                    |
| 37        | Scan Drive - 15 Volts                        | V    | N/A                   | -17        | -15       | -13         | N/A                    |
| 38        | Receiver +8 Volts                            | V    | N/A                   | +7         | +8        | +9          | N/A                    |
| 39        | Mixer/IF Amplifier +10 Volts                 | V    | N/A                   | +9         | +10       | +11         | N/A                    |
| 40        | Local Oscillator - Channel 1 +10 Volts       | V    | N/A                   | +9         | +10       | +11         | N/A                    |
| 41        | Local Oscillator - Channel 2 +10 Volts       | V    | N/A                   | +9         | +10       | +11         | N/A                    |
| 42        | A2 Quiet Bus Current                         | A    | N/A                   | N/A        |           | 1.25        | N/A                    |
| 43        | A2 Noisy Power Bus Current                   | A    | N/A                   | N/A        |           | 0.214       | N/A                    |

\* INSTRUMENT WITHIN SPECIFICATTON

@ Nominal values for reflector position (m & n) will be provided in Calibration LogBook. Nominal values for temperatures will be provided after completion of thermal balance test. All other nominal values will be provided after first Comprehensive Performance Test.

V = Vdc

A = Ampere

**CO = Counts**




Figure 2. EOS/AMSU - A2 Command / Status

The signal from each PRT is digitized via an A to D converter aboard the AMSU A instrument. During operation, the instrument provides a count from 0 to 32,768 representing the temperature of a given PRT. Calibration of the PRT circuits will be performed during system integration and test, which yields a discrete count vs. ohms relationship. This count to resistance relationship is made continuous via a third order polynomial fit to the data every 25 ohms, from 3725 ohms to 4600 ohms, for the in-flight warm calibration load (0.1K accuracy PRTs). The other instrument PRTs (0.5K accuracy) are represented by a polynomial fit to the data every 40 ohms from 1980 to 2380 ohms. The resulting equation gives the resistance as a function of counts (c) for a given  $i^{\text{th}}$  PRT:

$$R_i(c) = A_i c^3 + B_i c^2 + C_i c + D_i \quad \text{Equation 1}$$

Where:  $c$  = # of counts measured for  $i^{\text{th}}$  PRT  
 $A_i, B_i, C_i$  &  $D_i$  will be supplied in Cal Log Book

The Callendar-Van Dusen algorithm is then implemented once the resistance  $R_i(c)$  is known to determine the physical temperature of each  $i^{\text{th}}$  PRT. This equation is given by:

$$R_i = R_{oi} \left[ 1 + \alpha_i \left( t - \delta_i \left( \frac{t}{100} - 1 \right) \left( \frac{t}{100} \right) - \beta \left( \frac{t}{100} - 1 \right) \left( \frac{t}{100} \right)^3 \right) \right] \quad \text{Equation 3}$$

Where:

$T$  = physical temperature of PRT  
 $R_i$  = resistance (ohms) of  $i^{\text{th}}$  PRT (from equation 1)  
 $R_{oi}$  = resistance at ice point of  $i^{\text{th}}$  PRT (supplied by PRT vendor)  
 $\alpha_i, \delta_i$  = constants measured for  $i^{\text{th}}$  PRT (supplied by PRT vendor)  
 $\beta = 0$  (The in-flight PRT operating range is -10 C to +48 C for Instrument PRT and -15 C to 40 C for warm load PRT)

#### 2.2.1.2 Voltage and current data:

For voltage and current data (refer to data word 54 through 80, Table 3 and data word 32 through 43, Table 4), the measured parameter is defined by the linear functions:

Measured parameter,  $X = mN + b$

Where  $N$  is the data count reported for the parameter.

The  $m$  and  $b$  will be derived from the comprehensive and calibration performance testing and will be provided in calibration logbook.

### **2.2.1.3 Reflector Position:**

Reflector positions (refer to data word 11 & 12, Table 3 AMSU-A1 and data word 11, Table 4 AMSU-A2) are derived from antenna range testing. Antenna position for warm cal, cold cal, Nadir and full scan are determined at antenna range. The required antenna position data (Position vs Count) will be provided in the calibration log book.

### **2.2.2 DIGITAL TELEMETRY DATA**

Digital telemetry data (refer to data word 10, 11 & 12, Table 3 and 10 & 11, Table 4) transmitted from the EOS/AMSU-A instrument consists of command status, instrument modes, antenna power relay states, PLO lock status, ADC Latchup flag. The digital telemetry data are depicted in Figure 1 and Figure 2. Digital telemetry number 1 through 6 for both A1 and A2 is a response to the appropriate commands. Digital telemetry number 9 and 10 in Figure 1 for AMSU-A1 and number 8 in Figure 2 for AMSU-A2 provides the status of scanner power off or on. Number 8 telemetry in Figure 1 for AMSU-A1 indicates PLO #1 or PLO #2 is on or off. Telemetry number 11 and 12 provides PLO lock status. Digital telemetry 13 in Figure 1 and number 9 in Figure 2 provides ADC Latchup flag. PLO lock detect and ADC Latchup flag requires action. If PLO is not locked then redundant PLO needs to be selected. If ADC Latchup flag triggers then discard the data for that specific scan. Reset C&DH Processor (#7) is for command only and should be ignored.


### 2.2.3 DATA WORD FORMAT

Data word format is provided in Table 5

**Table 5 DATA WORD FORMAT**

|   | DATA WORD     |                    | 15 | 14 | 13 | 12 | 11 | 10 | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 |
|---|---------------|--------------------|----|----|----|----|----|----|---|---|---|---|---|---|---|---|---|---|
| For<br>A1<br><br>R<br>E<br>F<br>E<br>R<br><br>To<br>T<br>A<br>B<br>L<br>E<br>#3 | 10            | Command Status     | D  | D  | D  | D  | D  | X  | D | D | X | D | D | D | D | D | D | X |
|   | 11,12         | Reflector Position | D  | D  | D  | D  | D  | D  | D | D | D | D | D | D | D | D | X | O |
|   | 13 through 57 | Temp. Data         | D  | D  | D  | D  | D  | D  | D | D | D | D | D | D | D | D | D | O |
|   | 59 through 80 | Voltage & Current  | D  | D  | D  | D  | D  | D  | D | D | D | D | D | D | D | D | D | O |
| For<br>A2<br><br>R<br>E<br>F<br>E<br>R<br><br>To<br>T<br>A<br>B<br>L<br>E<br>#4 | 10            | Command Status     | D  | X  | X  | X  | D  | X  | X | D | X | D | D | D | D | D | D | X |
|   | 11            | Reflector Position | D  | D  | D  | D  | D  | D  | D | D | D | D | D | D | D | D | X | O |
|   | 12 through 30 | Temp. Data         | D  | D  | D  | D  | D  | D  | D | D | D | D | D | D | D | D | D | O |
|   | 32 through 43 | Voltage & Current  | D  | D  | D  | D  | D  | D  | D | D | D | D | D | D | D | D | D | O |

D = DATA  
X = IGNORE  
O = ZERO

|   |  |  |  |  |  |                      |  |
|---|--|--|--|--|--|----------------------|--|
|  <b>NASA</b><br>National Aeronautics and<br>Space Administration       |  |  |  | Report Documentation Page                                    |  |                      |  |
| 1. Report No.<br>---  |  | 2. Government Accession No.<br>---                       |  | 3. Recipient's Catalog No.<br>---                            |  |                      |  |
| 4. Title and Subtitle<br><br>Integrated Advanced Microwave Sounding Unit-A<br>(AMSU-A), Engineering Telemetry Description                               |  |  |  | 5. Report Date<br>August 2000                                |  |                      |  |
|   |  |  |  | 6. Performing Organization Code<br>---                       |  |                      |  |
| 7. Author(s)<br><br>M. Calderon   |  |  |  | 8. Performing Organization Report No.<br>10377C              |  |                      |  |
| 9. Performing Organization Name and Address<br>Aerojet<br>1100 W. Hollyvale<br>Azusa, CA 91702  |  |  |  | 10. Work Unit No.<br>---                                     |  |                      |  |
|   |  |  |  | 11. Contract or Grant No.<br>NAS 5-32314                     |  |                      |  |
| 12. Sponsoring Agency Name and Address<br>NASA<br>Goddard Space Flight Center<br>Greenbelt, Maryland 20771  |  |  |  | 13. Type of Report and Period Covered<br>Final               |  |                      |  |
|   |  |  |  | 14. Sponsoring Agency Code<br>---                            |  |                      |  |
| 15. Supplementary Notes<br><br>---  |  |  |  |  |  |                      |  |
| 18. ABSTRACT (Maximum 200 words )<br><br>This is the Engineering Telemetry Description, for the Integrated Advanced Microwave Sounding Unit-A (AMSU-A). |  |  |  |  |  |                      |  |
| 17. Key Words (Suggested by Author(s))<br><br>EOS<br>Microwave System   |  |  |  | 18. Distribution Statement<br><br>Unclassified --- Unlimited |  |                      |  |
| 19. Security Classif. (of this report)<br><br>Unclassified  |  | 20. Security Classif. (of this page)<br><br>Unclassified |  | 21. No. of pages   |  | 22. Price<br><br>--- |  |

NASA FORM 1626 OCT 86



PREPARATION OF THE REPORT DOCUMENTATION PAGE

The last page of a report facing the third cover is the Report Documentation Page, RDP. Information presented on this page is used in announcing and cataloging reports as well as preparing the cover and title page. Thus, it is important that the information be correct. Instructions for filling in each block of the form are as follows:

Block 1. Report No. NASA report series number, if preassigned.

Block 2. Government Accession No. Leave blank.

Block 3. Recipient's Catalog No. Reserved for use by each report recipient.

Block 4. Title and Subtitle. Typed in caps and lower case with dash or period separating subtitle from title.

Block 5. Report Date. Approximate month and year the report will be published.

Block 6. Performing Organization Code. Leave blank.

Block 7. Authors. Provide full names exactly as they are to appear on the title page. If applicable, the word editor should follow a name.

Block 8. Performing Organization Report No. NASA installation report control number and, if desired, the non-NASA performing organization report control number.

Block 9. Performing Organization Name and Address. Provide affiliation (NASA program office, NASA installation, or contractor name) of authors.

Block 10. Work Unit No. Provide Research and Technology Objectives and Plants (RTOP) number.

Block 11. Contract or Grant No. Provide when applicable.

Block 12. Sponsoring Agency Name and Address. National Aeronautics and Space Administration, Washington, D.C. 20546-0001. If contractor report, add NASA installation or HQ program office.

Block 13. Type of Report and Period Covered. NASA formal report series; for Contractor Report also list type (interim, final) and period covered when applicable.

Block 14. Sponsoring Agency Code. Leave blank.

Block 15. Supplementary Notes. Information not included

elsewhere: affiliation of authors if additional space is required for Block 9, notice of work sponsored by another agency, monitor of contract, information about supplements (file, data tapes, etc.) meeting site and date for presented papers, journal to which an article has been submitted, note of a report made from a thesis, appendix by author other than shown in Block 7.

Block 16. Abstract. The abstract should be informative rather than descriptive and should state the objectives of the investigation, the methods employed (e.g., simulation, experiment, or remote sensing), the results obtained, and the conclusions reached.

Block 17. Key Words. Identifying words or phrases to be used in cataloging the report.

Block 18. Distribution Statement. Indicate whether report is available to public or not. If not to be controlled, use "Unclassified-Unlimited." If controlled availability is required, list the category approved on the Document Availability Authorization Form (see NHB 2200.2, Form FF427). Also specify subject category (see "Table of Contents" in a current issue of STAR) in which report is to be distributed.

Block 19. Security Classification (of the report). Self-explanatory.

Block 20. Security Classification (of this page). Self-explanatory.

Block 21. No. of Pages. Count front matter pages beginning with iii, text pages including internal blank pages, and the RDP, but not the title page or the back of the title page.

Block 22. Price Code. If Block 18 shows "Unclassified-Unlimited," provide the NTIS price code (see "NTIS Price Schedules" in a current issue of STAR) and at the bottom of the form add either "For sale by the National Technical Information Service, Springfield, VA 22161-2171" or "For sale by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402-0001," whichever is appropriate.

|   |   |  |  |                                  |
|---|---|--|--|----------------------------------|
| <b>REPORT DOCUMENTATION PAGE</b>  |   |  | Form<br>Approved<br>OMB No.<br>0704-0188                                 |                                  |
| Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503. |   |  |  |                                  |
| 1. AGENCY USE ONLY (Leave blank)  |   | 2. REPORT DATE   |  | 3. REPORT TYPE AND DATES COVERED |
| 4. TITLE AND SUBTITLE<br><br>Integrated Advanced Microwave Sounding Unit-A (AMSU-A), Engineering Telemetry Description  |   |  | 5. FUNDING NUMBERS<br><br>NAS 5-32314                                    |                                  |
| 6. AUTHOR(S)<br><br>M. Calderon   |   |  |  |                                  |
| 7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)<br>Aerojet<br>1100 W. Hollyvale<br>Azusa, CA 91702   |   |  | 8. PERFORMING ORGANIZATION<br>REPORT NUMBER<br><br>10377C<br>August 2000 |                                  |
| 9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)<br>NASA<br>Goddard Space Flight Center<br>Greenbelt, Maryland 20771   |   |  | 10. SPONSORING/MONITORING<br>AGENCY REPORT NUMBER<br><br>---             |                                  |
| 11. SUPPLEMENTARY NOTES<br><br>---  |   |  |  |                                  |
| 12a. DISTRIBUTION/AVAILABILITY STATEMENT<br><br>---   |   |  | 12b. DISTRIBUTION CODE<br><br>---  |                                  |
| 13. ABSTRACT (Maximum 200 words)<br><br>This is the Engineering Telemetry Description, for the Integrated Advanced Microwave Sounding Unit-A (AMSU-A).  |   |  |  |                                  |
| 14. SUBJECT TERMS<br><br>EOS<br>Microwave System  |   |  | 15. NUMBER OF PAGES  |                                  |
|   |   |  | 16. PRICE CODE<br><br>---  |                                  |
| 17. SECURITY CLASSIFICATION<br>OF REPORT<br><br>Unclassified  | 18. SECURITY CLASSIFICATION<br>OF THIS PAGE<br><br>Unclassified | 19. SECURITY CLASSIFICATION<br>OF ABSTRACT<br><br>Unclassified | 20. LIMITATION OF<br>ABSTRACT<br><br>SAR                                 |                                  |

## GENERAL INSTRUCTIONS FOR COMPLETING SF 298

The Report Documentation Page (RDP) is used in announcing and cataloging reports. It is important that this information be consistent with the rest of the report, particularly the cover and title page. Instructions for filling in each block of the form follow. It is important to stay within the lines to meet optical scanning requirements.

Block 1. Agency Use Only (Leave blank)

Block 2. Report Date Full publication date including day, month, and year, if available (e.g., 1 Jan 88). Must cite at least the year.

Block 3. Type of Report and Dates Covered State whether report is interim, final, etc. If applicable, enter inclusive report dates (e.g., 10 Jun 87 - 30 Jun 88).

Block 4. Title and Subtitle A title is taken from the part of the report that provides the most meaningful and complete information. When a report is prepared in more than one volume report the primary title, add volume number and include subtitle for the specific volume. On classified documents enter the title classification in parentheses.

Block 5. Funding Numbers To include contract and grant numbers; may include program element number(s), project number(s), task number(s), and work unit number(s). Use the following labels:

|    |   |                 |    |   |                         |
|----|---|-----------------|----|---|-------------------------|
| C  | - | Contract        | PR | - | Project                 |
| G  | - | Grant           | TA | - | Task                    |
| PE | - | Program Element | WU | - | Work Unit Accession No. |

Block 6. Author(s) Name(s) of person(s) responsible for writing the report, performing the research, or credited with the content of the report. If editor or compiler, this should follow the name(s).

Block 7. Performing Organization Name(s) and Address(es) Self-explanatory.

Block 8. Performing Organization Report Number Enter the unique alphanumeric report number(s) assigned by the organization performing the report.

Block 9. Sponsoring/Monitoring Agency Name(s) and Address(es) Self-explanatory.

Block 10. Sponsoring/Monitoring Agency Reports Number (if known)

Block 11. Supplementary Notes Enter information not included elsewhere such as: Prepared in cooperation with ...; Trans. of ...; To be published in ... When a report is revised, include a statement whether the new report supersedes or supplements the older report.

Block 12.a Distribution/Availability Statement Denotes public availability or limitations. Cite any availability to the public. Enter additional limitations or special markings in all capitals (e.g., NOFORN, REL, ITAR).

DOD - See DoDD 5230.24 *Distribution Statement on Technical Documents*

DOE - See authorities.

NASA - See Handbook NHB 2200.2.

NTIS - Leave blank.

Block 12.b Distribution Code

DOD - Leave blank.

DOE - Enter DOE distribution categories from the standard Distribution for Unclassified Scientific and Technical Reports.

NASA - Leave blank.

NTIS - Leave blank.

Block 13. Abstract Include a brief *Maximum 200 words* factual summary of the most significant information contained in the report.

Block 14. Subject Terms Keywords or phrases identifying major subjects in the report.

Block 15. Number of Pages Enter the total number of pages.







Block 16. Price Code Enter appropriate price code (7TS only).

Block 17 - 19. Security Classifications Self-explanatory. Enter U.S. Security Classification in accordance with U.S. Security Regulations (i.e., UNCLASSIFIED). If form contains classified information, stamp classification on the top and bottom of the page.

Block 20. Limitation of Abstract This block must be completed to assign a limitation to the abstract. Enter either UL (unlimited) or SAR (same as report). An entry in this block is necessary if the abstract is to be limited. If blank, the abstract is assumed to be unlimited.



## DOCUMENT APPROVAL SHEET

|   |              |  |           |
|---|--------------|--|-----------|
| TITLE<br>Engineering Telemetry Description  |              | DOCUMENT NO.<br>Report 10377C<br>August 2000 |           |
| INPUT FROM:<br>M. Calderon  | CDRL:<br>305 | SPECIFICATION ENGINEER:<br>N/A               | DATE      |
| CHECKED BY:<br>N/A  | DATE         | JOB NUMBER:<br>N/A                           | DATE      |
| APPROVED SIGNATURES   |              | DEPT. NO.                                    | DATE      |
| Product Team Leader (A. Nieto) <u></u>                                 |              | 8410   | 25 Aug 00 |
| Systems Engineer (R. Platt) <u></u>                                    |              | 8410   | 8/24/00   |
| Design Assurance (E. Lorenz) <u></u>                                  |              | 8410   | 8/24/00   |
| Quality Assurance (R. Taylor) <u></u>                                |              | 7831   | 8/24/00   |
| PMO/Technical (P. Patel) <u></u>                                     |              | 8410   | 8/24/00   |
| <b>Released:</b><br>Configuration Management (J. Cavanaugh) <u></u> |              | 8410   | 8/28/00   |
| By my signature, I certify the above document has been reviewed by me and concurs with the technical requirements related to my area of responsibility. |              |  |           |
| (Data Center) FINAL   |              |  |           |
|   |              |  |           |
|   |              |  |           |

